

Method Statement

Date: 14/03/16	Review : 14/03/18	MS No: MD113	
Task: Use of Fire Training Trailer			
Area of Works: On site			
Resources			
Supervision: None required, service engineers trained to work unaccompanied and			
adhere to any on site local safety practices.			
Operatives: Senior service engineer (authorised and trained to work on training trailer)			
Equipment: Training trailer			
Source of ignition			
Substances: Assessments will be prepared and available on site and operatives have			
been fully briefed on the safe use of products.			
Training: Appropriate trade training			
Identified hazards (refer to relevant RAMS and COSHH data)			
MD112			
Method of Works:			
Trailer only to be towed by experienced and competent driver.			
Do not attempt reversing manoeuvres without the aid of a banksman.			
Trailer to be positioned on level, open ground. Maintain a safe distance of at least 4.5			
metres from any building, vehicles or any type of combustible material.			

Once positioned, the trailer must be braked and then detached from the towing vehicle. The towing vehicle must be moved to a safe distance from the trailer.

The operator must stand at a distance of not less than 3 metres from the trailer when carrying out demonstrations.

Students must stand at a distance of not less than 3 metres from the trailer during demonstrations.

Warn students prior to the use of the pyrotechnic flash simulator. Permit those with heart conditions or a nervous disposition to leave the are prior to the demonstration.

Regularly inspect the condition of hoses for signs of damage or detioration.

When unattended, gas cylinders to be turned off at the manual control valve.

Approved by	
	Chase Fire Protection Ltd